

## Measure lead TP-C1812B



The Measure lead TP-C1812B is a low noise differential measure lead designed to be used with the Handyscope HS4 DIFF, Handyscope HS6 DIFF and the ATS5004D and ATS610004D-XMSG. This 3 meter long measure lead splits in two individual ends of each 1.2 meter long. The BNC connector at one end plugs directly on the instrument. The two other ends each feature a single 4 mm banana plug, on which application specific test points, clamps or probes can be plugged.

The inputs of these instruments are differential, which means that both sides of the input have a high impedance. There is no connection to ground as in conventional oscilloscopes which are used with coax cables. Using a coax cable on the instrument would result in the instrument picking up a lot of external interference.

The specially designed Measure lead TP-C1812B has a high Common Mode Rejection Ratio (CMRR), it is very insensitive to external interfering signals. The two ends can be placed up to more than two meters apart, while picking up very little interference. With a conventional oscilloscope with a standard probe this is not possible. The maximum distance between the positive side and ground is then usually limited to approximately 20 cm. And this 20 cm is very susceptible to interference.

The Measure lead TP-C1812B is very flexible and uses a heat resistant silicone isolation that is also oil resistant. To ensure safety, the banana plugs are shrouded.

## Specifications

Connectors	
Instrument side	isolated male BNC connector
Test point side	red and black 4 mm shrouded banana plugs
Bandwidth	7 MHz
Safety	CAT III, 1000 V, double isolated
Dimensions	
Total length	3000 mm
Length to split	1800 mm
Length individual ends	1200 mm
Weight	100 g
Color	black
Certifications and compliances	
CE conformity	yes
RoHS	yes
Accessories	
Color coding rings	5 x 3 rings, various colors



**TiePie engineering**  
Koperslagersstraat 37  
8601 WL Sneek  
The Netherlands

Tel.: +31 515 415 416  
Fax: +31 515 418 819  
E-mail: [sales@tiepie.nl](mailto:sales@tiepie.nl)  
[www.tiepie.com](http://www.tiepie.com)



This information is subject to change without notice.  
Copyright © 2018 TiePie engineering. All rights reserved. Revision 1.3, August, 2018.