



Useful for:

- HS801
- HS508
- Handyscope 2
- Handyprobe 2



USB INTERFACE

With this USB interface, several TiePie measuring instruments can be plugged to a USB port. This USB interface is a simple and reliable solution for connecting TiePie measuring instruments to your (laptop) computer with a USB port.

The USB interface supports the following TiePie measuring instruments: HS508, HS801, HS801-AWG, Handyprobe model HP2 and Handyscope 2.

By connecting the measuring instruments to the USB port it becomes possible to connect more measuring instruments to one PC. The USB interface is supplied by the downstream port and does not need external power supply. Because of the long screws the USB interface can easily be coupled and uncoupled to the measuring instrument. The USB interface is delivered with drivers for Windows 95/98/ME and Windows NT/2000.

Technical specification

Technical data:

Connectors:	USB plug type A 25 pins female connector
Cable length:	1.8 meter / 70 inches
Power supply:	200 mAmp van downstream poort
Weight:	150 gram
Color:	black
Order code:	TP-USB25F



FOR MORE INFORMATION, DEMO SOFTWARE, SOFTWARE, SOURCE CODE AND DLL'S SEE ON OUR INTERNET PAGE: [HTTP://WWW.TIEPIE.N L](http://www.tiepie.nl)



TiePie engineering
Koperslagersstraat 37
8601 WL SNEEK
The Netherlands

Tel: + 31 515 415 416
Fax: + 31 515 418 819
E-mail: support@tiepie.nl
Web page: <http://www.tiepie.nl>